



Tractors Built for the Best™

**AGRICUBE**

**Tractors for specialists**

**Vigneto Largo Basso**



# Agricube Vigneto Largo Basso

## The perfect ally for those who want power and compactness

Carraro is becoming increasingly specialised in low profile versions and has now added the new Vigneto Largo Basso (VLB) version to the existing Frutteto Basso (FB) model. While maintaining the compact size of the Frutteto Basso (FB) tractor, the Vigneto Largo Basso (VLB) version has a 1155 mm front axle and a minimum overall width of 1350 mm (with both 20" and 24" wheels).

With its special characteristics, the Agricube Vigneto Largo Basso (VLB) is the perfect ally for those who want a tractor that combines power and reliability with a compact height and width.

This new model once again confirms Carraro's important role in the field of special orchard and vineyard tractors and its focus on the specific needs of Mediterranean agriculture.

The 24+12 version with electro-hydraulic reverser and electro-hydraulic Hi-Lo joins the classic 24+24 transmission with mechanical reverser and mechanical Hi-Lo. The 24+12 transmission has a synchronised electro-hydraulically activated PTO.

Designed by the Group Tractor Division, the Vigneto Largo Basso (VLB) is the result of close collaboration between the Carraro Engineering and Marketing Departments and the company's sales network which is responsive to its customers' demands. Information flows rapidly and directly from the customer to the manufacturer who will become increasingly important for future products.



<b>ENGINE</b>	<b>FPT, F5C EURO IIIa</b>	<b>FPT, F5C EURO IIIa</b>
Maximum power ISO kW/hp	55 kW / 74.8 hp	65 kW / 88.4 hp
Displacement and number of cylinders	3200 cc / 4 turbo	3200 cc / 4 turbo intercooler
<b>TRANSMISSION</b>		
<b>24 + 24</b> 24 forward gears 24 reverse gears	<b>Reverser:</b> Mechanical · <b>Hi-Lo:</b> Synchro · <b>Gear levers:</b> Lateral · <b>Gearbox:</b> 4 gear synchro · <b>Range:</b> 3 gear range L/M/Hi synchro <b>Tractor speed:</b> 40 km/h <b>Minimum speed of tractor:</b> 0.5 km/h	
<b>24 + 12 FWD-REV</b> 24 forward gears 12 reverse gears	<b>Reverser:</b> Electro-hydraulic · <b>Hi-Lo:</b> Electro-hydraulic · <b>Gear levers:</b> Lateral · <b>Gearbox:</b> 4 gear synchro · <b>Range:</b> 3 gear range L/M/Hi synchro <b>Tractor speed:</b> 40 km/h <b>Minimum speed of tractor:</b> 0.5 km/h	
<b>POWER TAKE-OFF</b>		
Speed (dry disc clutch)	540/540e - 540/1000 rpm	
Synchronised PTO	Optional for 24+24 / Standard for 24+12	
<b>HYDRAULIC SYSTEM</b>		
Maximum lifting capacity	2400 kg	
Distributors	2 Distributors: 1 SE/DE SRN + 1 SE/DE SRN (4 rear outlets) with 2 pumps	
Pump capacity with 2 pumps (standard configuration)	64.7 + 28.9 L/min	
<b>THREE-POINT HITCH</b>		
CAT 2/1/1N		
<b>DRIVER'S SEAT</b>		
Tiltable front roll bar		
<b>WHEELS</b>		
Front	280/70R16	
Rear	360/70R24	
<b>DIMENSIONS</b>		
Length (without ballast)	3840 mm	
Height	1000 mm at driving seat / 1250 mm bonnet / 2457 mm raised roll bar	
Wheelbase	2085 mm	
Overall width (min/max)	1350 mm/1577 mm	
<b>TABLE OF TYRE COMBINATIONS</b>		
Front - rear wheels	280/70R16 - 360/70R24	
	280/70R16 - 380/70R24	
	260/70R16 - 380/70R20	
	280/70R18 - 440/65R24	

#### Maximum width of tractor (metres)

1/1.1    1.1/1.2    1.2/1.3    1.3/1.4    1.4/1.5    1.5/1.6    1.6/1.7    1.7/1.8    1.8/1.9    1.9/2

  
**VLB 80/90hp**

  
**FB 80/90hp**



**Carraro SpA**

Via Olmo, 37  
35011 Campodarsego  
Italy  
Tel. +39 049 9219111  
Fax +39 049 9289111

**Carraro Tractors  
Service & Support**

Viale del lavoro, 1  
45100 Rovigo  
Italy  
Tel. +39 0425 403611  
Fax +39 0425 403674

**Carraro Tractors  
Sales & Engineering**

Via Trentino, 4/6  
35043 Monselice  
Italy  
Tel. +39 0429 1709111  
Fax +39 049 9289271

[info@carrarotracors.com](mailto:info@carrarotracors.com)

The information in this publication is provided for purely illustrative purposes; the manufacturer reserves the right to modify the models described without prior notice.

Drawings and photographs may refer to optional equipment or special options for other countries. For all other information, contact our sales network.